

Subpart G—Crew Spaces

§ 116.700 General requirements.

(a) A crew accommodation space and a work space must be of sufficient size, adequate construction, and with suitable equipment to provide for the safe operation of the vessel and the protection and accommodation of the crew in a manner practicable for the size, facilities, service, route, speed, and modes of operation of the vessel.

(b) The deck above a crew accommodation space must be located above the deepest load waterline.

§ 116.710 Overnight accommodations.

Overnight accommodations must be provided for all crew members if the vessel is operated more than 12 hours in a 24 hour period, unless the crew is put ashore and the vessel is provided with a new crew.

§ 116.730 Crew accommodations on vessels of more than 19.8 meters (65 feet) in length with overnight accommodations for more than 49 passengers.

A crew accommodation space on a vessel of more than 19.8 meters (65 feet) in length with overnight accommodations for more than 49 passengers must comply with §§ 72.20–10; 72.20–15; 72.20–20(d); 72.20–25 (a) and (d) 72.20–30; 72.20–35; 72.20–45; 72.20–50; and 72.20–55 in subchapter H of this chapter.

[CGD 85–080, 61 FR 900, Jan. 10, 1996, as amended by USCG–2000–7790, 65 FR 58462, Sept. 29, 2000; USCG–2002–13058, 67 FR 61729, Sept. 30, 2002]

Subpart H—Passenger Accommodations

§ 116.800 General requirements.

(a) All passenger accommodations must be arranged and equipped to provide for the safety of the passengers in consideration of the route, modes of operation, and speed of the vessel.

(b) The height of ceilings in a passenger accommodation space, including aisles and passageways, must be at least 1880 millimeters (74 inches), but may be reduced at the sides of a space to allow for camber, wiring, ventilation ducts, and piping.

(c) A passenger accommodation space must be maintained to minimize fire and safety hazards and to preserve sanitary conditions. Aisles must be kept clear of obstructions.

(d) A passenger accommodation space must not contain:

(1) Electrical generation equipment or transformers, high temperature parts, pipelines, rotating assemblies, or any other item that could injure a passenger, unless such an item is adequately shielded or isolated; or

(2) A control for operating the vessel, unless the control is so protected and located that operation of the vessel by a crew member will not be impeded by a passenger during normal or emergency operations.

(e) The deck above a passenger accommodation space must be located above the deepest load waterline.

(f) A variation from a requirement of this subpart may be authorized by the Commanding Officer, Marine Safety Center for an unusual arrangement or design provided there is no significant reduction of space, accessibility, safety, or sanitation.

§ 116.810 Overnight accommodations.

(a) A berth must be provided for each passenger authorized to be carried in overnight accommodation spaces. Each berth must measure at least 1880 millimeters (74 inches) by 610 millimeters (24 inches) and have at least 610 millimeters (24 inches) of clear space above.

(b) Berths must not be located more than three high and must be constructed of wood, fiber reinforced plastic, or metal. A berth located more than 1,525 millimeters (60 inches) above the deck must be fitted with a suitable aid for access.

(c) The construction and arrangement of berths and other furniture must allow free and unobstructed access to each berth. Each berth must be immediately adjacent to an aisle leading to a means of escape from the accommodation space. As aisle alongside a berth must be at least 610 millimeters (24 inches) wide. An aisle joining two or more aisles in an overnight accommodation space must be at least 1,065 millimeters (42 inches) wide.

[CGD 85–080, 61 FR 900, Jan. 10, 1996, as amended at 62 FR 51350, Sept. 30, 1997]